



































NOTE 1: FLOW MAY BE IN EITHER DIRECTION

NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.

NOTE 3: REFERENCE AWWA C-504-B & DRILLING (A.N.S.I. 250)

NOTE 4: NUMBER OF TURNS TO CLOSE = 103

NOTE 5: MANUAL POSITION INDICATOR

NOTE 7: B = (8) 2.0-4.5 UNC x 2.25 DEEP TAPPED HOLES EACH FLANGE

NOTE 8: "Z" = (1/16" OR .0625 RAISED FACE ON EACH FLANGE)

NOTE 9: RATED AND TESTED FOR 250 PSI WORKING PRESSURE

NOTE 10: APPROXIMATE WEIGHT = 6300lbs.



**KENNEDY VALVE**

Division of McWane, Inc.  
1021 EAST WATER STREET ELMIRA, NEW YORK 14901

DWN: D SKAKAL

DATE: 5/23/17

DWG. NO.

CAT914C10063-01

48" STYLE 1450

CLASS 250 BUTTERFLY VALVE

(AUMA GS250.3/GZ250.3:8 GEAR BOX)

HANDWHEEL OPERATOR &

EXTENDED BONNET - FE X FE ENDS