

KENNEDY VALVE

Division of McWane, Inc.

1021 East Water Street P.O. Box 931 Elmira, New York 14902-0931 Telephone (607) 734-2211 Fax (607) 734-1003

Certificate of Compliance

[K81A Guardian Fire Hydrants]

This is to certify that Guardian Fire Hydrants manufactured by Kennedy Valve, in our Elmira, New York, USA facility, meets all dimensional, material, and test specifications, per the latest edition of ANSI/AWWA C502 Standard for Dry Barrel Fire Hydrants.

All hydrants are tested at 500 psi seat and shell and are intended for service up to 250 psi in Water Works applications. The Kennedy K81A Guardian Fire Hydrant meets all application requirements of AWWA C502 and is typically offered when end users arrangement(s) fall outside the scope of the UL and/or FM specifications and rated for 250 psi service with an operating temperature maximum of 150° F. The machined sealing surfaces of flanged end inlets conform to the Manufactures Standardization Society, MSS Standard Practice SP-6 (Standard Finishes for Contact Faces of Pipe Flanges and Connecting-End Flanges of Valves and Fittings). Mechanical joint end inlets dimensions conform to ANSI/AWWA C111/A21.11.

The interior and exterior surfaces of the nozzle section receive a coating(s) of Ken-Guard thermosetting TGIC Polyester which provides exceptional durability and UV resistance. Interior and Exterior surfaces of Elbows produced at Kennedy Valve and supplied as a standard part of our fire hydrants, receive a heat fused, potable epoxy coating which conforms to AWWA C550, has been tested and accepted by Underwriter Laboratories (UL) and Listed by the National Sanitation Foundation (NSF) as meeting the NSF/ANSI 61 Drinking Water System Components Standard.

The interior surfaces (lower barrel and stem sections) are coated with an asphaltic coating, primer, or equivalent per AWWA C502 and are suitable for contact with drinking water. The exterior surfaces of the lower barrel are coated with the same material.

July 6, 2023

Daniel Burczynski Kennedy Valve Quality Manager