



KENNEDY VALVE

C509 KS FW OS&Y

RESILIENT SEATED GATE VALVE
FLANGED ENDS

SIZES 2" - 12"

Fig. 8068A



SIZE	A	B	C	D	E	F	G	H	Weight (lbs.)
12	14"	7"	19"	1-1/4"	40-5/8"	53-1/8"	12-7/8"	18"	581
10	13"	6-1/2"	16"	1-3/16"	35-3/8"	45-3/4"	12-7/8"	18"	427
8	11-1/2"	5-3/4"	13-1/2"	1-1/8"	29-1/4"	37-3/4"	8-3/4"	14"	253
6	10-1/2"	5-1/4"	11"	1"	23-3/4"	30-1/8"	8-3/4"	12"	152
4	9"	4-1/2"	9"	15/16"	18-1/4"	22-3/4"	8-5/8"	10"	105
3	8"	4"	7-1/2"	3/4"	15-5/8"	18-7/8"	4-5/8"	10"	64
2-1/2	7-1/2"	3-3/4"	7"	11/16"	13-7/8"	16-3/8"	4-5/8"	7-1/4"	51
2	7"	3-1/2"	6"	5/8"	12"	10"	4-5/8"	7-1/4"	N/A

DIMENSIONS

