



KENNEDY VALVE

C515 KS RW NON-RISEING RESILIENT SEATED GATE VALVE FLANGED ENDS SIZES 2" - 12"

Fig. 7561ASS (with handwheel)

Fig. 7561ANSS (with nut)

Fig. 7701ASS (with post plate, 2"-12")



AWWA

LISTED

APPROVED

All flange valves tapped & plugged @ Position "A"

STD. TAP SIZE
1/2": 2-1/2" - 4"
3/4": 6" - 12"

DIMENSIONS										
SIZE	A	B	C	D	E	F	G	H	Weight (lbs.)	
2	7"	3-1/2"	6"	11/16"	10-7/8"	4-5/8"	7-1/4"	2"	41	
2-1/2	7-1/2"	3-3/4"	7"	11/16"	11-3/8"	4-5/8"	7-1/4"	2-1/2"	49	
3	8"	4"	7-1/2"	3/4"	12-3/8"	4-5/8"	10"	3"	62	
4	9"	4-1/2"	9"	15/16"	14-3/4"	8-5/8"	10"	4-1/4"	99	
6	10-1/2"	5-1/4"	11"	1"	19"	8-3/4"	12"	6-1/4"	142	
8	11-1/2"	5-3/4"	13-1/2"	1-1/8"	22-1/2"	8-3/4"	14"	8-1/4"	239	
10	13"	6-1/2"	16"	1-3/16"	26-1/2"	12-7/8"	18"	10-1/4"	408	
12	14"	7"	19"	1-1/4"	30"	12-7/8"	18"	12-1/4"	554	

Note: Add 16 lbs. for Indicator Post Plate (3"-12" only)

Kennedy Valve | 1021 E Water St, Elmira, NY 14901

